

ioDrive Duo™



- > Sustain over 250,000 I/Os per second
- > Easily RAID multiple ioDrive Duo's
- > Half length easily fits most servers

WWW.FUSIONIO.COM

ioDrive Duo Capacity	320GB	640GB	640GB	1.28TB
NAND Type	SLC (Single Level Cell)	SLC (Single Level Cell)	MLC (Multi Level Cell)	MLC (Multi Level Cell)
Read Bandwidth (64kB)	1.5 GB/s	1.5 GB/s	1.5 GB/s	1.5 GB/s
Write Bandwidth (64kB)	1.5 GB/s	1.5 GB/s	1.0 GB/s	1.1 GB/s
Read IOPS (512 Byte)	261,000	273,000	196,000	185,000
Write IOPS (512 Byte)	262,000	252,000	285,000	278,000
Mixed IOPS (75/25 r/w)	238,000	236,000	138,000	150,000
Access Latency (512 Byte)	26 µs	26 µs	29 µs	30 µs
Bus Interface	PCI-Express x4 / x8 or PCI Express 2.0 x4			
Operating Systems	64-Bit Microsoft XP/Vista/Win7/Server 2003/Server 2008, RHEL 4/5/6, SLES 10/11, OEL v5, VMware ESX 4.0/4.1/ESXi 4.1, Solaris 10 U8/U9			

AGENCY

US / Canada	ANSI C63.4/EN 55022/ CNS 13438, Radiated and Conducted Emissions Class A EN 55024 Immunity EN 55022 Class A
Europe	2004/108/EC EMC Directive CE IEC 61000 Class A Mark
Japan	VCCI - V-2/2009.04
Taiwan	BSMI - CNS 13438 / EN 55022 class A
New Zealand/Australia	AS/NZS CISPR22:2006 / 47CFR Part 15, Radiated and Conducted Emissions Class A
Korea	KCC – FIO-IODRIVE DUO (Class A)
RoHS	RoHS – EU Directive 2002/95/EC

STANDARDS


Form Factor	Full height, Half length PCI Express 2.0
Connectivity	PCI Express electromechanical spec 2.0
Power	PCI Express power spec 2.0

ENVIRONMENTAL SPECIFICATIONS

		Min	Max
Temperature (°C)*	Operational	0	55
	Non-operational	-40	70
Air Flow (LFM)		300	
Humidity (%)	Non-condensing	5	95
	Operational		10,000
Altitude (ft)	Operational		10,000
	Non-operational		30,000

* Temperature derated 1 C per 1000 ft elevation above sea level

100% Designed and Assembled in the U.S.A.



FUSION-io®